

AIRFLOW MEASUREMENT WITH TEMPERATURE AND ALARM CAPABILITY



PRODUCT HIGHLIGHTS

- “Plug and Play” operation
- EBTRON exclusive bead-in-glass thermistor sensors
- NIST traceable calibration
- 0 to 3,000 FPM calibrated range with percent-of-reading accuracy
- Cost effective single probe
- Airflow and status alarm
- Temperature output capability
- Analog and RS-485 output models
- Dry contact relay
- Remote transmitter with LCD display
- Actual (CFM) or mass (SCFM) airflow measurement
- Velocity-weighted temperature measurement between -20° F to 160° F
- Smart *Sensor Detection System (SDS)* continuously monitors for sensor and transmitter faults
- Standard FEP plenum rated cable between sensor probes and transmitter
- Three-year warranty
- Toll-free customer support for the lifetime of the product

TYPICAL APPLICATIONS

- High performance CV/VAV terminal box measurement
- Small duct outdoor air delivery monitoring
- Small duct airflow tracking
- Hospital pressurization
- Laboratory pressurization

EBTRON ADVANCED THERMAL DISPERSION TECHNOLOGY

EBTRON pioneered bead-in-glass thermistor based thermal dispersion over 40 years ago. EBTRON’s thermal dispersion technology relates the power dissipated by a self-heated thermistor to the airflow rate at one or more sensor nodes in an airstream. All EBTRON airflow monitoring systems use this time-tested thermal dispersion technology.

MODEL DESCRIPTION

The EF-x2000-T is EBTRON’s measurement solution for round ducts between 4 and 16 inches in diameter when a remote display is desired. Ideal for small duct airflow measurement and airflow tracking applications. The EF-x2000-T’s remote transmitter and user interface provides more customization than the EF-x1000-T.

EF-x2000-T TECHNICAL SPECIFICATIONS

General

Probe and Sensor Node Configurations

- 1 probe x 1 sensor node/probe (4 inch [101.6 mm] probe)
- 1 probe x 2 sensor nodes/probe (5 to 16 inch [127.0 to 406.4 mm] probes)

Installed Airflow Accuracy¹

±3% of reading

Sensor Node Averaging Method

- Airflow:** Independent arithmetic average
- Temperature:** Independent, velocity weighted average

Listings and Compliance

- UL:** 60730-1, 60730-2-9; CAN E60730-1, E60730-2-9 (EF-A2000-T Only)
- FCC:** This device complies with Part 15 of the FCC rules
- RoHS:** This device is RoHS2 compliant

Environmental Limits

Temperature:

- Probes 0 to 2,000 fpm** [0 to 10.16 m/s]:
-20 to 160 °F [-28.9 to 71.1 °C]
- Probes 0 to 3,000 fpm** [0 to 15.24 m/s]:
0 to 160 °F [-17.8 to 71.1 °C]
- Transmitter:** -20 to 120 °F [-28.9 to 48.9 °C]

Humidity: (non-condensing)

- Probes:** 0 to 100%
- Transmitter:** 5 to 95%

Individual Sensing Nodes

Sensing Node Sensors

- Self-heated sensor:** Precision, hermetically sealed, bead-in-glass thermistor probe
- Temperature sensor:** Precision, hermetically sealed, bead-in-glass thermistor probe

Sensing Node Housing

- Material:** Glass-filled Polypropylene (Kynar[®] with /SS option)
- Sensor Potting Materials:** Waterproof marine epoxy

Sensing Node Internal Wiring

Type: Kynar[®] coated copper

Airflow Measurement

- Accuracy:** ±3% of reading to NIST-traceable volumetric airflow standards (includes transmitter uncertainty)
- Calibrated Range:** 0 to 3,000 FPM [0 to 15.24 m/s]
- Calibration Points:** 7

Temperature Measurement

- Type:** Velocity-weighted average
- Accuracy:** ±0.15°F [0.08 °C] to NIST-traceable temperature standards (includes transmitter uncertainty)
- Calibrated Range:** -20 to 160 °F [-28.9 to 71.1 °C]
- Calibration Points:** 3

Sensor Probe Assembly

Tube

Material: Mill finish 6063 aluminum (316 stainless steel with /SS option)

Mounting Brackets

Material: 304 stainless steel

Mounting Options & Size Limits

Insertion: 4, 5, 6, 7, 8, 9, 10, 12, 14, and 16 inch round [101.6, 127.0, 152.4, 177.8, 203.2, 228.6, 254.0, 304.8, 355.6 & 406.4 mm]

Probe to Transmitter Cables

Type: FEP jacket, plenum rated CMP/FT6/CL2P, UL/cUL listed, -67 to 302 °F [-55 to 150 °C], UV tolerant

Standard Lengths: 3, 10, 25 and 50 ft. [0.9, 3.1, 7.6 and 15.2 m]

Connecting Plug: 0.60" [15.24 mm] nominal diameter

Transmitter

Power Requirement: 24 VAC (22.8 to 26.4 under load) @8V-A

User Interface: 16-character LCD display and 4 button interface

B.A.S. Connectivity Options

EF-A2000 Transmitter: Two field selectable (0-5/1-5/0-10/2-10 VDC*), scalable and protected analog output signals (AO1=airflow, AO2 = temperature or alarm)

* The VDC output circuit of the EF-A2000 transmitter can drive the input circuit of devices designed to measure 4-wire current loops with a resistive load ≥250 ohms.

EF-N2000 Transmitter: One field selectable (BACnet MS/TP or Modbus RTU) and non-isolated RS-485 network connection - Individual sensor node airflow rates and temperatures are available via the network (provide individual 24 VAC transformers at each EF-N2000 transmitter for applications requiring isolated RS-485)

Relay

Type: Dry Contact w/ onboard jumper to drive a remote LED (R1=alarm)

Status: N.O. or N.C. via user setup configuration

Rating: 30 VDC or 24 VAC @ 3 amp. max.

Airflow Alarm

Type: Low and/or high user defined setpoint alarm

Tolerance: User defined % of setpoint

Delay: User defined

Zero Disable: Alarm can be disabled when the airflow rate falls below the low limit cutoff value (unoccupied periods)

Reset Method: Manual or automatic

Visual Indication: Yes, LCD display

Network Indication: Yes (EF-N2000 only)

Analog Signal Indication: Yes, on AO2 assignment (EF-A2000 only)

Contact Closure Relay: Yes, on R1 assignment

System Status Alarm

Type: Sensor diagnostic system trouble indication

Visual Indication: Yes, LCD display

Network Indication: Yes (EF-N2000 only)

Analog Signal Indication: Yes, on AO2 assignment (EF-A2000 only)

Contact Closure Relay: Yes, on R1 assignment

¹ Installed airflow accuracy is the actual system accuracy expected and includes sampling uncertainty of the sensor probes when installation meets or exceeds placement guidelines.