

AIRFLOW MEASUREMENT WITH TEMPERATURE AND ALARM CAPABILITY



PRODUCT HIGHLIGHTS

- “Plug and Play” operation
- EBTRON exclusive bead-in-glass thermistor sensors
- Sensor nodes are individually calibrated at 16 airflow rates to NIST traceable standards
- 0 to 5,000 FPM calibrated range with percent-of-reading accuracy
- Airflow and status alarm
- Temperature output capability
- Analog and RS-485 output models
- Three mounting styles
- Remote transmitter with LCD display
- Actual (CFM) or mass (SCFM) airflow measurement
- Velocity-weighted temperature measurement between -20° F to 160° F
- Smart *Sensor Detection System (SDS)* continuously monitors for sensor and transmitter faults
- Independent test data demonstrates resistance to saltwater and chemical exposure
- Standard FEP plenum rated cable between sensor probes and transmitter
- Three-year warranty
- Toll-free customer support for the lifetime of the product

TYPICAL APPLICATIONS

- Outdoor airflow monitoring
- Small duct airflow tracking
- Hospital pressurization
- Laboratory pressurization
- Air change verification and monitoring
- Differential airflow tracking and pressure control
- System performance monitoring

EBTRON ADVANCED THERMAL DISPERSION TECHNOLOGY

EBTRON pioneered bead-in-glass thermistor based thermal dispersion over 40 years ago. EBTRON’s thermal dispersion technology relates the power dissipated by a self-heated thermistor to the airflow rate at one or more sensor nodes in an airstream. All EBTRON airflow monitoring systems use this time-tested thermal dispersion technology.

MODEL DESCRIPTION

The HTx104-P is EBTRON’s most economical solution for larger systems when “out-of-the-box” installed accuracy is not required and field adjustment is acceptable. Perfect for LEED outdoor air delivery monitoring or other low sensor density airflow measurement applications. The HTx104-P transmitter has isolated outputs with a true 4-20mA output option (HTA104-P)

HTx104-P TECHNICAL SPECIFICATIONS

General

Probe and Sensor Node Configurations (max.)

Type A Transmitter: 1 probe x 4 sensor nodes/probe

Type B Transmitter: 2 probes x 2 sensor nodes/probe

Installed Airflow Accuracy¹

≤ 2 sq.ft. [0.185 sq.m.]: ±3% of reading

> 2 sq.ft. [0.185 sq.m.]: ±(3% to 10%), typical (increases with increasing duct size). May be improved by field adjustment using the Field Adjust Wizard (FAW) to a reliable reference.

PE Sensor Density: Refer to the PE sensor density table.

Sensor Node Averaging Method

Airflow: Independent, arithmetic average

Temperature: Independent, velocity weighted average

Listings and Compliance

UL: 60730-1; CAN/CSA-E60730-1

CE: Yes

UKCA: Yes

BACnet International: BTL Listed (HTN104 transmitter)

FCC: This device complies with Part 15 of the FCC rules

RoHS: This device is RoHS2 compliant

Environmental Limits

Temperature:

Probes: -20 to 160 °F [-28.9 to 71.1 °C]

Transmitter: -20 to 120 °F [-28.9 to 48.9 °C]

Humidity: (non-condensing)

Probes: 0 to 100%

Transmitter: 5 to 95%

Individual Sensing Nodes

Sensing Node Sensors

Self-heated sensor: Precision, hermetically sealed, bead-in-glass thermistor probe

Temperature sensor: Precision, hermetically sealed, bead-in-glass thermistor probe

Sensing Node Housing

Material: Glass-filled Polypropylene (Kynar® with /SS option)

Sensor Potting Materials: Waterproof marine epoxy

Sensing Node Internal Wiring

Type: Kynar® coated copper

Airflow Measurement

Accuracy: ±2% of reading to NIST-traceable airflow standards (includes transmitter uncertainty)

Calibrated Range: 0 to 5,000 fpm [0 to 25.4 m/s]

Calibration Points: 16

Temperature Measurement

Type: Velocity-weighted average

Accuracy: ±0.15 °F [0.08 °C] to NIST-traceable temperature standards (includes transmitter uncertainty)

Calibrated Range: -20 to 160 °F [-28.9 to 71.1 °C]

Calibration Points: 3

Sensor Probe Assembly

Tube

Material: Gold anodized 6063 aluminum (316 stainless steel with /SS option)

Mounting Brackets

Material: 304 stainless steel

Mounting Options & Standard Size Limits¹

Insertion: 6 to 191 in. [152.4 to 4851 mm]

Stand-off: 6 to 190 in. [152.4 to 4826 mm]

Internal: 8 to 194 in. [203.2 to 4928 mm]

Probe to Transmitter Cables

Type: FEP jacket, plenum rated CMP/FT6/CL2P, UL/cUL listed, -67 to 302 °F [-55 to 150 °C], UV tolerant

Standard Lengths: 10, 15, 20, 25, 30, 40 and 50 ft. [3.1, 4.6, 6.1, 7.6, 9.1, 12.2 and 15.2 m]

Connecting Plug: 0.60" [15.24 mm] circular DIN

Transmitter

Power Requirement: 24 VAC (22.8 to 26.4 under load) @11V-A

PCB Connections: Gold-plated PCB interconnects and test points

User Interface: 16-character LCD display and 4 button interface

B.A.S. Connectivity Options

HTA104 Transmitter: Two field selectable (0-5/0-10 VDC or 4-20mA), scalable and isolated analog output signals (AO1=airflow, AO2=temperature or alarm)

HTN104 Transmitter: One field selectable (BACnet MS/TP or Modbus RTU) and isolated RS-485 network connection- Individual sensor node airflow rates and temperatures are available via the network

Airflow Alarm

Type: Low and/or high user defined setpoint alarm

Tolerance: User defined % of setpoint

Delay: User defined

Zero Disable: Alarm can be disabled when the airflow rate falls below the low limit cutoff value (unoccupied periods)

Reset Method: Manual or automatic

Visual Indication: Yes, LCD display

Network Indication: Yes (HTN104 only)

Analog Signal Indication: Yes, on AO2 assignment (HTA104 only)

System Status Alarm

Type: Sensor diagnostic system trouble indication

Visual Indication: Yes, LCD display

Network Indication: Yes (HTN104 only)

Analog Signal Indication: Yes, on AO2 assignment (HTA104 only)

¹ Installed airflow accuracy allows for additional uncertainty that results from averaging a finite number of sensors in a contorted velocity profile created from up and downstream disturbances. The specified installed accuracy is based on the PE sensor density rules for installations that meet or exceed EBTRON minimum placement requirements. PE sensor density rules may not be available for all duct sizes due to sensor placement limitations.