



GTx116e-PC/H

GTx116e-PC

GTx116e-P+

HTx104-PE

Sensor Nodes

up to 16

up to 16

up to 16

up to 4

Measurement Output

Airflow
Temperature
Relative Humidity*
Enthalpy*
Dew Point*
*Available on /H option only

Airflow
Temperature

Airflow
Temperature

Airflow
Temperature

Accuracy

Airflow: $\pm 2\%$ of reading to NIST-traceable airflow standards
Temperature: $\pm 0.15^\circ\text{F}$ [0.08°C] to NIST-traceable temperature standards
Humidity: @ 77°F [25°C], 20-80% RH: $\pm 2\%$ RH, 0-20 and 80-100% RH: $\pm 3.5\%$ RH

Connectivity Options (Model code placeholder x= A, C, F, M, N, or U)

Linear Analog Output Signals (A01, A02, A03)

A, C, F, M, U

A, C, F, M, U

A, C, F, M, U

A

Note: A03 is only available on GTx116e when the /H option is selected for RH.

BACnet MS/ TP or Modbus RTU

C

C

C

N

BACnet Ethernet or BACnet IP, Modbus TCP and TCP/IP

M

M

M

LonWorks Free Topology

F

F

F

USB "Thumb Drive" Datalogger

U

U

U

NIST Traceable Calibration



Alarms



EB-Link App



Mounting Styles

Insertion
Internal
Stand-off

Insertion
Internal
Stand-off

Insertion
Internal
Stand-off

Insertion
Internal
Stand-off