



FAN-IQ

AIR-IQ

AIR-IQ2

Sensor Nodes

up to 8

up to 16

up to 16

Measurement Output

Airflow
Temperature

Airflow
Temperature
Relative Humidity
Enthalpy
Dew Point

Airflow
Temperature
Relative Humidity
Enthalpy
Dew Point

Accuracy

Airflow: $\pm 2\%$ of reading to NIST-traceable airflow standards
 Temperature: $\pm 0.15^\circ\text{F}$ [0.08°C] to NIST-traceable temperature standards
 Humidity: @ 77°F [25°C], 20-80% RH: $\pm 2\%$ RH, 0-20 and 80-100% RH: $\pm 3.5\%$ RH

Airflow Series

GTx108e-F

GTx116e-PC

GTx116e-PC

Connectivity Options (Model code placeholder x= A, C, F, M, N, or U)

Linear Analog Output Signals (A01, A02, A03) Note: A03 is only available on GTx116e when the /H option is selected for RH.

A

A

A

BACnet MS/ TP or Modbus RTU

C

C

C

BACnet Ethernet or BACnet IP, Modbus TCP and TCP/IP

M

M

M

LonWorks Free Topology

F

F

F

USB "Thumb Drive" Datalogger

U

U

U

NIST Traceable Calibration



Alarms



EB-Link App

